


## Application to anchorage for demanded tensile load up to perm. 90 kN

The threads of our Formwork Sleeves DW15/DW20 made of aluminium or steel are formed by rolling. Thereby a precisely formed thread is produced - needed for optimal tensile load transmission.

Care for demanded concrete pressure property before straining the anchorage ! General load performance specifications are not possible, since these depend on the individual installation situations: concrete quality, age and pressure strength !

Formwork Sleeves DW15/DW20 also are available in Non Corrosive Steel A4 on request.



**Formwork Sleeve Alu DW15** total length 15 cm in formwork greater than 20 cm  
perm. P 90°: 26 kN/17 N/mm<sup>2</sup> 401515 2,600 kg

**Formwork Sleeve St DW15** total length 19 cm in formwork greater than 25 cm  
perm. P 45°: 60 kN/17 N/mm<sup>2</sup> 501519 8,600 kg

**Formwork Sleeve St DW15** total length 29 cm in formwork greater than 35 cm  
perm. P 45°: 85 kN/17 N/mm<sup>2</sup> - 90 kN/30 N/mm<sup>2</sup> 501529 13,100 kg

### Assembly Parts



**Cone Plug** Ø 42 mm, for requested concrete cover 12 mm, supplied with **double-head nail 75 mm**, for careful stripping and reusing Cone Plug, 4 markings in 90° for accurate positioning 401518 1,700



**Magnetic Cone** Ø 42 mm, reusable, for concrete cover 12 mm, installation into **steel formwork** - suitable to all of our Formwork Sleeves DW15, Magnetic Load 0,8 kN supplied with 5 mm Allen Key for easy removing 401521 0,150 **on request**




**Sealing Plug PVC** Ø 31 mm 131518 0,250



**Sealing Cone Plug SBK 15/10** made of casted concrete optimal solution to exposed concrete construction quick clueing with 2C-Inject-Gun 411510 3,100



**Fixation Cone 45° PVC** for installation of Formwork Sleeves in 45°-angularity (types in other angularity available on request) Anchorage in 45° angularity can be constructed out of walls. Drilling through the formwork not necessary !



401551 0,250

Application in formworks greater than 25 cm



**Recess PE 45°** Ø 40 mm for **installation in wet concrete surfaces in 45°- angularity** The anchor point can easily planed over and recognized again

401509 0,015

PU: 100 pcs/cart., Prices p. pc., ex warehouse