Anchorage EhS 45° "Hercules" DW26.5

The powerful and quick reanchoring to support frames for single-sided formwork!

The new developed slim shaped anchor-head can be easily installed through close-meshed reinforcement and the sealed PVC duct tube prevents concrete foam penetrating. Also there is no contact of steel to the surface.

Benefits:

- Quick, simple and correct assembly:
 - fastening at the upper meshes with the Holder 45°
- No coupling parts required
- Tie rods DW26.5 reusable
- Short and slim shaped, light weight
- minimises refinishing
- Version for ready grinded surface in range



"Hercules" EsB with Holder 45°

perm. load P 45° / concrete pressure property : 275 kN / 18 N/mm² - 290 kN / 20 N/mm² - 325 kN / 25 N/mm²



Anchorage EhS 45° "Hercules" DW26.5/EsB total length 60 cm installation in slabs with subsequent screed coating thickness greater than 40 cm

- type with sealed fitted PVC duct tube and sealing cap, supplied ready for installation -

Art.-No. 502651 1,100 kg

Installation with Holder 45° - Art.-No. 502661, lost part or with Adjusting-Gadget 45°, Art.-No. 515201, reusable > see special page


Anchorage EhS 45° "Hercules" DW26.5/GIB total length 50 cm installation in slabs with ready grinded surface thickness greater than 40 cm

- type with Recess "PE-45°" and indicating pointer -

The area can be easily planed over and recognized again. The Recess leaves a suitable large space for any filling compound.

Art.-No. 502652 1,100 kg

Installation with Holder 45° - Art.-No. 502661 - exclusively



Holder 45°

for installing anchorage in 45° angularity to wall formwork Sturdy mounting with broad bearing. Clamp in PVC duct tube and tight wing nut.





Stop Plug

for sealing the PVC duct tube respectively trapping filling compound.

Art.-No. 502670 0,600 kg

PU 100 pcs.

Prices per piece, ex warehouse, add.VAT



